

- NOTES:
- DESIGN AND INTERFACE SMA PER I. D. S. -20, AND MMCX PER I. D. S. -33.
 - MARKED: 2033-1180-OOP.
 - JAM NUT, LOCK WASHER & "O"-RING SUPPLIED LOOSE.
 - IP67 WHEN IN MATED OR UN-MATED CONDITION.

| PARTS | MATERIALS | FINISH |
|----------------|------------------------------------|--|
| BODY & JAM NUT | STAINLESS STEEL QQ-S-763/S-764 | PASSIVATION |
| CONTACT | BE. CU. ASTM-B-196 | .000030 GOLD |
| LOCK WASHER | BRONZE ASTM-B-591 | NICKEL PER QQ-N-290, CLASS 1, GRADE G |
| INSULATOR | TEFLON, ASTM-D-1710 | |
| O-RINGS | SILICON RUBBER; PER ASTM-D-2000 | |

| REV. | DESCRIPTION | DATE | APPR. |
|------|---------------|----------|-------|
| A | PER ECN 11427 | 08/30/12 | JEM |


PALCO CONNECTOR

22 GREAT HILL RD., NAUGATUCK, CT 06770

UNLESS OTHERWISE SPECIFIED, PALCO WORKMANSHIP STANDARDS APPLY
 TOLERANCES ON: DECIMALS: XX ± .01 .XXX ± .005 ANGLES ±1/2° 32'
 DIMENSIONS IN INCHES OR (METRIC) DO NOT SCALE PRINTS

CATALOG ITEM

| DRAWN | CHECKED | ENGINEER | APPROVED | FSCM |
|----------|---------|--------------|----------|--------------|
| JEM | MS | JEM | MS | 58167 |
| DATE | | DRAWING NO. | | PLATING OPT. |
| 04/26/12 | | 2033-1180-00 | | P |



DESCRIPTION FRONT MOUNT ADAPTOR
SMA JACK TO MMCX JACK