



NOTES:

1. DESIGN AND INTERFACE PER I. D. S. -40.
2. NUT, WASHER AND GASKET ARE SHIPPED LOOSE.
3. MUST MEET A 14.5 PSI (10 METER), 2 MINUTES LEAK TEST. (TEST 5 COMPLETE CONNECTORS PER LOT).
4. "D" MOUNTING HOLE PER DS-16A, FIG. 10.

E	PER ECN 12591	08/22/17	JEM	<h1 style="margin: 0;">PALCO CONNECTOR</h1> <p style="margin: 0;">22 GREAT HILL RD., NAUGATUCK, CT 06770</p> <p style="margin: 0;">UNLESS OTHERWISE SPECIFIED, PALCO WORKMANSHIP STANDARDS APPLY</p> <p style="margin: 0;">TOLERANCES ON: DECIMALS: XX $\pm .01$.XXX $\pm .005$ ANGLES $\pm 1/2^\circ$ 32$\sqrt{}$</p> <p style="margin: 0;">DIMENSIONS IN INCHES OR (METRIC) DO NOT SCALE PRINTS</p>	DRAWN	CHECKED	ENGINEER	APPROVED	FSCM	
D	PER ECN 9798	02/16/09	JEM		EK	JEM	HN	JEM	58167	
C	PER ECN 9089	01/07/08	JEM		DESCRIPTION BNC, WATERPROOF JACK, BULKHEAD, PC MOUNT					
B	PER ECN 8859	03/13/07	JEM							
A	PER ECN 8360	02/06/06	JEM		DATE	DRAWING NO.	PLATING OPT.			
REV.	DESCRIPTION	DATE	APPR.	FSR # 6594;	11/22/05	40-1475-01	E			