



FILE NAME: MC283-16.dwg

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS    DECIMALS    ANGLES $\pm 1/64$ $.XX \pm .01$ $\pm 1/2^\circ$ $.XXX \pm .003$	CONTRACT NO.		<b>MIL-CON™</b> AN AFFILIATE OF THE PHOENIX COMPANY OF CHICAGO		
	APPROVALS	DATE	MC283-16 AUDIO CONNECTOR		
THE INFORMATION DISCLOSED IN THIS DOCUMENT IS CONFIDENTIAL AND PROPRIETARY TO MIL-CON, INC. AND MAY NOT BE USED FOR MANUFACTURE OR ANY OTHER PURPOSE WITHOUT THE WRITTEN CONSENT OF MIL-CON, INC.	DRAWN A.G.	12/13/90	SIZE A	FSCM NO. 63525	DWG. NO. SD: MC283-16
	CHECKED A. Huevo	11/13/06	ISSUED		REV. B
DO NOT SCALE DRAWING			SCALE NONE		SHEET 1 OF 2

SPECIFICATIONS:

- 1) MATERIALS:  
SHELL AND PANEL NUT: STAINLESS STEEL  
CONTACTS: COPPER ALLOY  
INSULATOR: DIALLYL PHTHALATE PER MIL-M-14, TYPE MDG
- 2) FINISHES/COLOR:  
SHELL AND PANEL NUT: PASSIVATED, SAND BLASTED  
CONTACTS: .000030 GOLD PER MIL-G-45204, TYPE II,  
CLASS 0; OVER .000100 NICKEL PER QQ-N-290  
INSULATOR: BLUE
- 3) ELECTRICAL PROPERTIES:  
OPERATING VOLTAGE: 60 VOLTS MAXIMUM POTENTIAL  
CURRENT RATING: 0.5 AMPS MAXIMUM  
DIELECTRIC BREAKDOWN: 500 VOLTS RMS  
INSULATION RESISTANCE: 1000 MEGOHMS MINIMUM  
CONTACT RESISTANCE (MATED): 0.04 OHMS MAXIMUM
- 4) MECHANICAL PROPERTIES:  
AIR PRESSURE: 2.5 P.S.I.  
WATER IMMERSION: 48 HOURS AT 6 FEET  
DURABILITY: 3000 CYCLES, MATE AND UNMATE
- 5) MC283-16 RECEPTACLE MATES WITH:  
MC617 - ALL VERSIONS  
MC329 - ALL VERSIONS
- 6) DIMENSIONS ARE FOR REFERENCE ONLY, UNLESS OTHERWISE SPECIFIED

<b>MIL-CON</b> <sup>TM</sup>	FILE NAME: MC283-16.dwg			
	SIZE	FSCM NO.	DWG. NO.	REV.
	A	63525	SD: MC283-16	B
DRAWN A.G.	SCALE	NONE	SHEET 2	OF 2
ISSUED				